

GITI TIRE CATALOGUE

GITI TIRE ANHUI COMPANY LTD.

This version is applied for HOANG LAN BINH CO., LTD only.



Giti



With special design and compound for only use of trailer or semi-trailer.
All these tyres in these catalogue cannot be used for lorries truck and buses.



Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road

Size	PR	Load Index (133/133 G)	Speed Rating	Standard Rim	Maximum Load		Maximum Pressure		Tread Depth (mm)	Outer Diameter (mm)	Section width (mm)	TL/TT
					kg	lbs	kPa	psi				
205/65R17.5	20PR	132/130 (133/133 G)	K(G)	6.00	1850/1750	4080/3860	900/900	130/130	11.5	711	205	TL
215/75R17.5	16PR	136/134	J	6.00	2240/2120	4940/4675	900/900	130/130	12.5	767	211	TL
235/75R17.5	18PR	143/141 (146/146)	J(F)	6.75	2725/2575	6005/5675	860/860	125/125	13.0	797	233	TL
245/70R17.5	16PR	143/141 (146/146)	J(F)	7.50	2725/2575	6005/5675	875/875	127/127	13	789	248	TL
245/70R19.5	18PR	141/140	J	7.50	2575/2500	5675/5510	860/860	125/125	14	839	248	TL
265/70R19.5	18PR	143/141	J	7.50	2725/2575	6005/5675	850/850	123/123	14.5	867	262	TL
285/70R19.5	18PR	150/148	J	8.25	3350/3150	7390/6940	900/900	130/130	14	895	283	TL
275/70R22.5	18PR	148/145 (152/148)	M(J)	8.25	3150/2900	6940/6395	900/900	130/130	14.2	958	276	TL
385/55R22.5	20PR	160/-(158/-)	K(L)	12.25	4500	9920	900	131	14.8	996	386	TL
425/65R22.5	20PR	165/-	K	12.25	5150	11400	830	120	15.3	1124	422	TL
*385/65R22.5	20PR	164/-(158/-)	K(L)	11.75	5000	11000	900	130	15.5	1072	389	TL

* GTL919+

*This product cannot be used for lorries truck and buses.



GTL919/GTL919+



Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road

Size	PR	Load Index	Speed Rating	Standard Rim	Maximum Load		Maximum Pressure		Tread Depth (mm)	Outer Diameter (mm)	Section width (mm)	TL/TT
					kg	lbs	kPa	psi				
12R22.5	18PR	152/149	M	9.00	3550/3250	7830/7160	930/930	135/135	23	1096	300	TL
315/60R22.5	20PR	154/148	L	9.75	3750/3150	8270/6940	900/900	130/130	18.0	950	313	TL

**This product cannot be used for lorries truck and buses.*



GDR672Z

GAR868S



Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road



Size	PR	Load Index	Speed Rating	Standard Rim	Maximum Load		Maximum Pressure		Tread Depth (mm)	Outer Diameter (mm)	Section width (mm)	TL/TT
					kg	lbs	kPa	psi				
11.00R20	18PR	152/149	K	8	3550/3250	7830/7160	930/930	135/135	15.0	1085	293	TT

**This product cannot be used for lorries truck and buses.*

GSR237



Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road



Size	PR	Load Index	Speed Rating	Standard Rim	Maximum Load		Maximum Pressure		Tread Depth (mm)	Outer Diameter (mm)	Section width (mm)	TL/TT
					kg	lbs	kPa	psi				
11R22.5	18PR	149/146	M	8.25	3250/3000	7160/6610	930/930	135/135	16.0	1054	279	TT

**This product cannot be used for lorries truck and buses.*

GSR256/GSR256M



Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road



Size	PR	Load Index	Speed Rating	Standard Rim	Maximum Load		Maximum Pressure		Tread Depth (mm)	Outer Diameter (mm)	Section width (mm)	TL/TT
					kg	lbs	kPa	psi				
295/80R22.5	18PR	154/149	M	9	3750/3250	8270/7160	850/850	123/123	16.5	1044	298	TL
12R22.5	18PR	152/149	L	9	3550/3250	7830/7160	930/930	135/135	17.5	1085	300	TL

**This product cannot be used for lorries truck and buses.*

NEW

GDM270

Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road



Size	PR	Load Index	Speed Rating	Standard Rim	Maximum Load		Maximum Pressure		Tread Depth (mm)	Outer Diameter (mm)	Section width (mm)	TL/TT
					kg	lbs	kPa	psi				
12.00R20	20PR	156/153	J	8.5	4000/3650	8820/8050	900/900	130/130	21.0	1136	315	TT

****This product cannot be used for lorries truck and buses.****

GDM670

Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road



Size	PR	Load Index	Speed Rating	Standard Rim	Maximum Load		Maximum Pressure		Tread Depth (mm)	Outer Diameter (mm)	Section width (mm)	TL/TT
					kg	lbs	kPa	psi				
11.00R20	18PR	152/149	K	8	3550/3250	7830/7160	930/930	135/135	20.0	1096	293	TT
12.00R20	20PR	156/153	J	8.5	4000/3650	8820/8050	900/900	130/130	20.0	1136	315	TT

****This product cannot be used for lorries truck and buses.****

GDM661 ★

Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road



Size	PR	Load Index	Speed Rating	Standard Rim	Maximum Load		Maximum Pressure		Tread Depth (mm)	Outer Diameter (mm)	Section width (mm)	TL/TT
					kg	lbs	kPa	psi				
12.00R20	20PR	156/153	K	8.5	4000/3650	8820/8050	900/900	130/130	18.0	1125	315	TT

****This product cannot be used for lorries truck and buses.****

GAM853



Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road



Size	PR	Load Index	Speed Rating	Standard Rim	Maximum Load		Maximum Pressure		Tread Depth (mm)	Outer Diameter (mm)	Section width (mm)	TL/TT
					kg	lbs	kPa	psi				
11.00R20	18PR	152/149	K	8	3550/3250	7830/7160	930/930	135/135	16.0	1085	293	TT
12.00R20	20PR	156/153	K	8.5	4000/3650	8820/8050	900/900	130/130	16.0	1125	315	TT

**This product cannot be used for lorries truck and buses.*

GAM871



Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road



Size	PR	Load Index	Speed Rating	Standard Rim	Maximum Load		Maximum Pressure		Tread Depth (mm)	Outer Diameter (mm)	Section width (mm)	TL/TT
					kg	lbs	kPa	psi				
12R22.5	20PR	154/151	L	9.00	3750/3450	8270/7810	930/930	135/135	18	1085	300	TL

**This product cannot be used for lorries truck and buses.*

GSR225



Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road



Size	PR	Load Index	Speed Rating	Standard Rim	Maximum Load		Maximum Pressure		Tread Depth (mm)	Outer Diameter (mm)	Section width (mm)	TL/TT
					kg	lbs	kPa	psi				
11R22.5	16PR	148/145	M	8.25	3150/2900	6940/6395	850/850	123/123	15.3	1050	279	TL

**This product cannot be used for lorries truck and buses.*



GITI TIRE ANHUI COMPANY LTD.
NO. 18, SHIXIN ROAD, HEFEI ECO-TECH DEVELOPMENT ZONE,
HEFEI, ANHUI PROVINCE, CHINA 230601
<https://www.vn.fleet.giti.com>