



GITI TIRE CATALOGUE

GITI TIRE GLOBAL TRADING PTE.LTD.

This version is applied for HOANG LAN BINH CO., LTD only.

With special design and compound for only use of trailer or semi-trailer.

All these tyres in these catalogue cannot be used for lorries truck and buses.

Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road



Size	PR	Load Index	Speed Rating	Standard Rim	Maximum Load		Maximum Pressure		Tread Depth (mm)	Outer Diameter (mm)	Section width (mm)	TL/TT
					kg	lbs	kPa	psi				
12R22.5	18PR	152/149	M	9.00	3550/3250	7830/7160	930/930	135/135	23	1096	300	TL

**This product cannot be used for lorries truck and buses.*



GDR672Z



GDM270

Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road



Size	PR	Load Index	Speed Rating	Standard Rim	Maximum Load		Maximum Pressure		Tread Depth (mm)	Outer Diameter (mm)	Section width (mm)	TL/TT
					kg	lbs	kPa	psi				
12.00R20	20PR	156/153	J	8.5	4000/3650	8820/8050	900/900	130/130	21.0	1136	315	TT

**This product cannot be used for lorries truck and buses.*

GSR237

Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road



Size	PR	Load Index	Speed Rating	Standard Rim	Maximum Load		Maximum Pressure		Tread Depth (mm)	Outer Diameter (mm)	Section width (mm)	TL/TT
					kg	lbs	kPa	psi				
11R22.5	18PR	149/146	M	8.25	3250/3000	7160/6610	930/930	135/135	16.0	1054	279	TL

**This product cannot be used for lorries truck and buses.*

GSR256/GSR256M

Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road



Size	PR	Load Index	Speed Rating	Standard Rim	Maximum Load		Maximum Pressure		Tread Depth (mm)	Outer Diameter (mm)	Section width (mm)	TL/TT
					kg	lbs	kPa	psi				
295/80R22.5	18PR	154/149	M	9	3750/3250	8270/7160	850/850	123/123	16.5	1044	298	TL
12R22.5	18PR	152/149	M	9	3550/3250	7830/7160	930/930	135/135	17.5	1085	300	TL

**This product cannot be used for lorries truck and buses.*

GDM661★

Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road



Size	PR	Load Index	Speed Rating	Standard Rim	Maximum Load		Maximum Pressure		Tread Depth (mm)	Outer Diameter (mm)	Section width (mm)	TL/TT
					kg	lbs	kPa	psi				
12.00R20	22PR	158/155	K	8.5	4250/3875	8820/8050	970/970	130/130	18.0	1125	315	TT

****This product cannot be used for lorries truck and buses.**

GDM670

Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road



Size	PR	Load Index	Speed Rating	Standard Rim	Maximum Load		Maximum Pressure		Tread Depth (mm)	Outer Diameter (mm)	Section width (mm)	TL/TT
					kg	lbs	kPa	psi				
11.00R20	18PR	152/149	K	8	3550/3250	7830/7160	930/930	135/135	20.0	1096	293	TT
12.00R20	20PR	156/153	J	8.5	4000/3650	8820/8050	900/900	130/130	20.0	1136	315	TT

****This product cannot be used for lorries truck and buses.**

GAM853

Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road



Size	PR	Load Index	Speed Rating	Standard Rim	Maximum Load		Maximum Pressure		Tread Depth (mm)	Outer Diameter (mm)	Section width (mm)	TL/TT
					kg	lbs	kPa	psi				
11.00R20	18PR	152/149	K	8	3550/3250	7830/7160	930/930	135/135	16.0	1085	293	TT
12.00R20	20PR	156/153	K	8.5	4000/3650	8820/8050	900/900	130/130	16.0	1125	315	TT
12.00R20	22PR	158/155	K	8.5	4250/3875	8820/8050	970/970	130/130	16.0	1125	315	TT

****This product cannot be used for lorries truck and buses.**

GAR868S

Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road



Size	PR	Load Index	Speed Rating	Standard Rim	Maximum Load		Maximum Pressure		Tread Depth (mm)	Outer Diameter (mm)	Section width (mm)	TL/TT
					kg	lbs	kPa	psi				
11.00R20	18PR	152/149	K	8	3550/3250	7830/7160	930/930	135/135	15.0	1085	293	TT

****This product cannot be used for lorries truck and buses. "**

GAM871

Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road



Size	PR	Load Index	Speed Rating	Standard Rim	Maximum Load		Maximum Pressure		Tread Depth (mm)	Outer Diameter (mm)	Section width (mm)	TL/TT
					kg	lbs	kPa	psi				
12R22.5	20PR	154/151	L	9.00	3750/3450	8270/7810	930/930	135/135	18	1085	300	TL
12R22.5	18PR	157/154	L	9.00	4125/3750	9090/8270	930/930	135/135	18	1085	300	TL

****This product cannot be used for lorries truck and buses. "**

